

# relook

## Advanced Solutions 4 You

### HD 5000+ Twin Tuner

relook newest generation of High definition receiver supporting IP applications and PVR Functions using MPEG-2 & MPEG-4 decoding technology, delivering Crystal clear audiovisual superior quality.

The New relook generation is set for the standards of the future, providing integral TV and Media connectivity designated to reproduce of MPEG 2, MPEG 4, DivX, XviD, AVI SSF, MP3, WAV, AIFF, WMA, Ogg, Vorbis, JPEG; BMP; TIFF; GIF; PNG Using HDMI , HDCP and USB 2.0.

The unique model HD-5000+ is equipped with wifi connection to grant an easy setup.

All relook models are equipped with Ethernet connection to allow you as a user: Stream your Favorit Internet TV and Radio, Read E-mail's, Browsing internet, update software, GOGO List Download.

GOGO List – The enhanced Software developed exclusively by relook allow you as a user to download from our website: organized channel list, Link to streamed TV and Radio channels consult new available channels on internet and satellite.

#### Main feature HD 5000+

- Modular Tuner , Plug & Play (Satellite HD, Cable HD, Terrestrial HD)
- Also available in combo models (Satellite HD + Terrestrial HD and Satellite HD + ATSC)
- High definition MPEG 4 DVB compliant, compatible standard definition as well
- PVR Internal & support for External HDD including Time Shift function
- 14 digit VFD Display 9 buttons, 2 x CA + 2 x CI
- SW updates over : Internet or USB 2.0 (rear + Front panel)
- Network communication via Ethernet & WIFI for easy setup
- File Sharing over Local Area Network using Samba
- Internet applications as TV & Radio streaming, read your E-mail, RSS NEWS (over IP)
- 7 days EPG (Extended Electronic Program guide)
- Karaoke player
- GOGO LIST channel list download support.



# HD-5000+ Twin Tuner

**HD-5000 S + T**

**HD-5000 S + C**

**HD-5000 C + T**

**HD-5000 S + ATSC**

## Product Information & Special features

- Modular Tuner, Plug & Play (Satellite HD, Cable HD, Terrestrial HD)
- Also available in combo models (Satellite HD + Terrestrial HD and Satellite HD + ATSC)
- High definition MPEG 4 DVB compliant, compatible standard definition as well
- PVR Internal & support for External HDD including Time Shift function
- 14 digit VFD Display 9 buttons, 2 x CA + 2 x CI
- SW updates over : Internet or USB 2.0 (rear + Front panel)
- Network communication via Ethernet & WIFI for easy setup
- File Sharing over Local Area Network using Samba
- Internet applications as TV & Radio streaming, read your E-mail, RSS NEWS (over IP)
- 7 days EPG (Extended Electronic Program guide)
- Karaoke player
- GOGO LIST channel list download support.

## System

- Processor: Sigma SMP 8634LF
- Flash Memory: 32 MB
- EEPROM: 256 KB
- SDRAM: 256 MB

## Video & Audio Decoding

- Transport stream: MPEG-2/MPEG-4 Part10 AVC/H.264 HD HP@L4.0 1920x1080 @ 50Hz (MPEG-2 ISO/IEC 13818 Transport stream Specification)
- Profile Level: MPEG-2 MP@HL, MPEG-4 Part10 AVC/H.264 HD MP@L4.0
- Input Rate: Maximum 90Mb/s
- Aspect Ratio: 4:3, Letter Box, 16:9, Pan & Scan

- Video Resolution: 1920x1080i, 1280x720p, 720x576i/p
- Audio Decoding: Dolby Digital, MPEG-1 Layer 1,2
- Audio Mode: Mono, Left, Right, Stereo, Dolby Digital bit-streams
- Media Player Video: MPEG 1 MPEG 2 MPEG 4 DivX XviD (with MP3 or PCM) AVI SSF (supported subtitle formats)
- Media Player Audio: MP3; WAV; AIFF; WMA; Ogg Vorbis
- Media Player Images: JPEG; BMP; TIFF; GIF; PNG

## Connectivity

### Frontal Panel:

- 1 USB 2.0
- 14 Digit VFD Display
- 9 buttons (Ok, Channel Up, Channel Down, Volume Up, Volume Down, Menu, Exit, LAN)
- 2 Smartcard reader
- 2 Commun Interfaces
- Available LAN indicator with possibility of Manual reset

### Rear Panel:

- HDMI with HDCP
- 1 USB 2.0
- Wireless antenna
- Ethernet RJ45
- Serial Port: RS-232C
- TV Scart
- VCR Scart
- YPbPr (Component Video)
- Optical Digital Audio Output Spdif
- RF Modulator

## Physical Specification:

### Size

- 340 X 220 X 65 mm (WXDXH)
- Operating Temperature: 0 degree C ~ 60 degree C
- Storage Temperature: -20 degree C ~ 75 degree C

### Power Supply

- Input Voltage: 90VAC ~ 240VAC / Power
- Type: SMPS(Switching Mode Power Supply)
- Power consumption: Maximum 40Watts
- Protection: Separate Internal Fuse



GT-SAT International S.A.R.L, Rue Millewee, L-7257 Helmsange Walferdange, Luxembourg;  
Tel: +352-26432203; Fax: +352-26432204; E-mail: info@gt-sat.com

GT-Sat reserves the right to amend, omit, change or add products, product-lines and features without notice.