

```

      AAAA          AAAA          FFFFFFFFFFFFFFFFFFFFFFFF
      AAAAAA      AAAAAA      FFFFFFFFFFFFFFFFFFFFFFFF
      AAAAAAAA      AAAAAAAA      FFFFFFFFFFFFFFFFFFFFFFFF
      AAA  AAA      AAA  AAA      FFF
      AAA  AAA      AAA  AAA      FFF
      AAA  AAA      AAA  AAA      FFF
      AAAAAAAAAAAAAA  AAAAAAAAAAAAAA  FFFFFFFFFF
      AAAAAAAAAAAAAA  AAAAAAAAAAAAAA  FFFFFFFFFF
      AAA      AAA  AAA      AAA  FFF
      AAA      AAA  AAA      AAA  FFF
      AAA      AAA  AAA      AAA  FFF

```

AAF Digital HD FORUM
www.aaf-board.com

AAF IMAGE 2.0c
Kathrein UFS910 - Kernel 2.6.17.14_stm22_0037 (15:45:04).

BusyBox v1.2.1 (2007.10.12-18:30+0000) Built-in shell (ash)
Enter 'help' for a list of built-in commands.

```

# /data/emu/newcs.sh
Icon cnewcs wird gestartet does not exist!
This is NewCS 1.62 - the New CardServer by the Butter-team..
Compiled on Aug 27 2008 at 16:53:09
Reading Config file from /data/keys/newcs.xml
TCP-log password is enabled, set to: NewCSpwd
TCP-log set to simple mode
level: normal
type: init
output: console,tcp
logger config: level 1 type 3 output 5
Console log options: level 1 type 3
TCP log options: level 1 type 3
[ 15:45:38 ] [ Box detect ] Box type 9 (Kathrein (ST) HD Box)
[ 15:45:38 ] [ Config ] Option <blockc0> for device 0 (USB0) not present, default
ting to NO
[ 15:45:38 ] [ Config ] Value in <ipk> for device 0 (USB0) is INVALID, skipping.
..
[ 15:45:38 ] [ Config ] Value in <ucpk> for device 0 (USB0) is INVALID, skipping
...
[ 15:45:38 ] [ Config ] Pincode for device 0 (USB0): 0000
[ 15:45:38 ] [ Config ] /dev/ttyUSB0 ECM priority: round
[ 15:45:38 ] [ httpd ] httpd-user: newcs, password: newcs, accesslevel: admin
[ 15:45:38 ] [ EMM Cache ] Initialising dynamic Cache
[ 15:45:38 ] [ ECM Cache ] Initialising dynamic Cache
[ NewCS ] Process ID is: 2279
[ 15:45:38 ] [ Loader ] Starting Telnet on port 1001
Can't create server: Address already in use
[ 15:45:38 ] [ Loader ] Reader type 2 on node /dev/ttyUSB0
[ 15:45:38 ] [ Phoenix ] Opening device /dev/ttyUSB0
[ 15:45:38 ] [ Phoenix ] Setting Parity to: ODD
[ 15:45:38 ] [ Phoenix ] Setting 2 Stop bits on node /dev/ttyUSB0
[ 15:45:38 ] [ Phoenix ] Setting Baud to custom 16129
[ 15:45:39 ] [ Phoenix ] Inverse RESET on node /dev/ttyUSB0
[ 15:45:41 ] [ Loader ] Reset failed ...
[ 15:45:41 ] [ Loader ] Starting Newcamd Server on port 15000
[ 15:45:41 ] [ NewCS ] Ready to GO! :)
[ 15:45:41 ] [ Newcamd ] Newcamd thread Server started on port 15000
# Icon cnewcs gestartet - wait does not exist!

```

[15:45:41] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:41] [Phoenix] Opening device /dev/ttyUSB0
[15:45:41] [Phoenix] Setting Parity to: ODD
[15:45:41] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:41] [Phoenix] Setting Baud to custom 16129
[15:45:41] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:42] [Loader] Reset failed ...
[15:45:42] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:43] [Phoenix] Opening device /dev/ttyUSB0
[15:45:43] [Phoenix] Setting Parity to: ODD
[15:45:43] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:43] [Phoenix] Setting Baud to custom 16129
[15:45:43] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:44] [Loader] Reset failed ...
[15:45:44] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:45] [Phoenix] Opening device /dev/ttyUSB0
[15:45:45] [Phoenix] Setting Parity to: ODD
[15:45:45] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:45] [Phoenix] Setting Baud to custom 16129
[15:45:45] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:46] [Loader] Reset failed ...
[15:45:46] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:47] [Phoenix] Opening device /dev/ttyUSB0
[15:45:47] [Phoenix] Setting Parity to: ODD
[15:45:47] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:47] [Phoenix] Setting Baud to custom 16129
[15:45:47] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:48] [Loader] Reset failed ...
[15:45:48] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:49] [Phoenix] Opening device /dev/ttyUSB0
[15:45:49] [Phoenix] Setting Parity to: ODD
[15:45:49] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:49] [Phoenix] Setting Baud to custom 16129
[15:45:49] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:50] [Loader] Reset failed ...
[15:45:50] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:51] [Phoenix] Opening device /dev/ttyUSB0
[15:45:51] [Phoenix] Setting Parity to: ODD
[15:45:51] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:51] [Phoenix] Setting Baud to custom 16129
[15:45:51] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:52] [Loader] Reset failed ...
[15:45:52] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:53] [Phoenix] Opening device /dev/ttyUSB0
[15:45:53] [Phoenix] Setting Parity to: ODD
[15:45:53] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:53] [Phoenix] Setting Baud to custom 16129
[15:45:53] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:54] [Loader] Reset failed ...
[15:45:54] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:55] [Phoenix] Opening device /dev/ttyUSB0
[15:45:55] [Phoenix] Setting Parity to: ODD
[15:45:55] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:55] [Phoenix] Setting Baud to custom 16129
[15:45:55] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:56] [Loader] Reset failed ...
[15:45:57] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:57] [Phoenix] Opening device /dev/ttyUSB0
[15:45:57] [Phoenix] Setting Parity to: ODD
[15:45:57] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:57] [Phoenix] Setting Baud to custom 16129
[15:45:57] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:45:58] [Loader] Reset failed ...

[15:45:59] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:45:59] [Phoenix] Opening device /dev/ttyUSB0
[15:45:59] [Phoenix] Setting Parity to: ODD
[15:45:59] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:45:59] [Phoenix] Setting Baud to custom 16129
[15:45:59] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:46:00] [Loader] Reset failed ...
[15:46:01] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:46:01] [Phoenix] Opening device /dev/ttyUSB0
[15:46:01] [Phoenix] Setting Parity to: ODD
[15:46:01] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:46:01] [Phoenix] Setting Baud to custom 16129
[15:46:01] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:46:02] [Loader] Reset failed ...
[15:46:03] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:46:03] [Phoenix] Opening device /dev/ttyUSB0
[15:46:03] [Phoenix] Setting Parity to: ODD
[15:46:03] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:46:03] [Phoenix] Setting Baud to custom 16129
[15:46:03] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:46:04] [Loader] Reset failed ...
[15:46:05] [Loader] Reader type 2 on node /dev/ttyUSB0
[15:46:05] [Phoenix] Opening device /dev/ttyUSB0
[15:46:05] [Phoenix] Setting Parity to: ODD
[15:46:05] [Phoenix] Setting 2 Stop bits on node /dev/ttyUSB0
[15:46:05] [Phoenix] Setting Baud to custom 16129
[15:46:05] [Phoenix] Inverse RESET on node /dev/ttyUSB0
[15:46:06] [Loader] Reset failed ...